

Architecture & Engineering Services For Homes

Village of Dobbs Ferry AHRB Report

Property Address

4 Brookside Lane Dobbs Ferry NY 10522

SUBMISSION REQUIREMENTS FOR SMALL SCOPE PROJECTS


<u>Definition of a Small Scope Project</u>: The modification of existing structures that do not affect height, bulk, mass, square footage, footprint, or roof structure; including, but not limited to: the construction, reconstruction, replacement or alteration of any elevation, façade, storefront, window, door or fence. This shall also include any freestanding or retaining wall with an exposed face or facade exceeding 30" in height at any place along the wall.

Applicant Name:	John Kilroe		_ Date Filed:	October 12, 202								
roperty Address: 4 Brookside Ln Dobbs Ferry 10522												
Check Application T	ype (may be more than one	:):										
☑ Façade Change	☐ Storefront	oors	☐ Fence or Wall									
Description of Propo New Kitchen Reno <u>Windows & Siding</u>	vation and new basemen	t renovation at existin	g single-famil	y dwelling.								

A copy of this completed form is to be included as a cover sheet for submissions to the AHRB.

In the table below, please indicate the type of submission by checking the applicable box or boxes indicated. Items denoted • in the column below your project type are the minimum required items for a complete application to the AHRB. Please indicate the type of submission. Please indicate by initialing each box in the appropriate column confirming that the information has been submitted. Do not initial for items if they are not included.

The AHRB reserves the right to ask for any additional information as specified on this form, if not included in the initial application, and may deem the application incomplete and not ready for review until this information is included. Resubmissions should reflect all comments made at the previous meeting and should be indicated with a note or a bubble on the plan, and shall include any additional requested information.




Plan Submittal Form

Address: _	4	Brookside Ln Dobbs Ferry 10522	
Applicatio	n #:	A2022-0059	
Project:	4	Brookside Ln Dobbs Ferry 10522	
Name:	J	ohn Scavelli, PE	
Email:	J	ohn@resreal.com	
Phone:		014-330-7712	
Plans attac	ched	d are being submitted for (check appropriate box):	
	X	Building permit application 1 PDF copy & 2 paper copies ¼ scale Amendment to an application or permit, 2 sealed copies Final As Built to close permit, 1 sealed copy Final survey to close permit, 1 sealed copy	
		d are submitted at the direction of the Building Inspector for review by thrd (check all that apply):	e
		BOT- 1 PDF copy + 5 paper copies ¼ scale PB - 1 PDF copy + 4 paper copies ¼ scale ZBA - 1 PDF copy + 4 paper copies ¼ scale AHRB - 1 PDF copy + 2 paper copies ¼ scale	
Received S	Stan	mp:	



PROJECT SITE - 4 BROOKSIDE LANE





PROJECT SITE - 4 BROOKSIDE LANE





STREET VIEW - 4 BROOKSIDE LANE






www.ResReal.com



LEFT ADJACENT HOUSE – 8 BROOKSIDE LANE





HOUSE ACROSS STREET RIGHT- 11 SHADY LANE





HOUSE ACROSS STREET – 20 SHADY LANE



The future of exterior cladding is here.

With CERTAplank® Reinforced Siding you're getting a product that combines durability and strength with the aesthetics and authentic feeling of real wood. CERTAplank siding is also far lighter, easier to handle, and more weather-resistant than real wood, fiber cement and wood composite siding. On top of that, it has the low cost to install and maintain of vinyl siding and a Lifetime Limited Warranty. With these benefits, CERTAplank outperforms the competition.

Emulates the look and feel of real wood.



Lightweight

12-foot panels are easy to handle and transport and allow for one person installation.



Fits all Standard 3/4" Accessories

You have full access to the broadest array of trim available.



Single 7" Exposure

Wide, flat face recreates the classic look of real wood siding.



Secure Lock

Post-formed positive lock with RigidForm technology and rollover nail hem.

Colors shown throughout this brochure are as accurate as printing methods will permit. Please see product samples before making final selection.

Reinforced Foam Backer

Combined with an extra thick panel to create rigidity and durability you'd expect from a hardboard cladding.

Style and color.

CERTAplank Single 7" is a wide, flat face profile that replicates the look of wood siding and is available in 10 low-gloss designer colors in an authentic woodgrain finish. PermaColor" Lifetime Fade Protection ensures that CERTAplank siding will look new for the life of the product.

Deluxe Colors

Forest*

Pacific Blue*

Charcoal Gray*

Cranite Gray

Sterling Gray

Savannah Wicker

Colonial White





200 SERIES




EXTERIOR & INTERIOR OPTIONS

Our Perma-Shield® exterior cladding system offers low maintenance and durability while providing an attractive appearance.

WINDOW EXTERIOR COLORS



PATIO DOOR EXTERIOR COLORS



INTERIOR OPTIONS





GLASS OPTIONS

 $Glass\ can\ affect\ energy\ efficiency\ more\ than\ any\ other\ part\ of\ a\ window\ or\ patio\ door\ -\ and\ not\ all\ glass\ performs\ the\ same.$ Andersen offers one of the industry's widest array of glass options, so you're sure to find the right choice for your climate and your home. Check with your supplier for the selections that meet ENERGY STAR® requirements in your area.

		ENERGY									LIGHT							
GLASS		U-Factor How well a product prevents theat from excaping.				Solar Heat Gain Coefficient How well a product blocks heat cassed by sunlight.			Visible Light Transmittance How much visible light comes through a product				UV Protection How well is product blocks altraviolet rays.					
SmartSun"	Thermal control similar to tinted glass, with visible light transmittance similar to Low-E glass.	0	0		D	0	0	0		0	0	0	D		0	0	0	
SmartSun with HeatLock® Coating	Applied to the room-side surface, it reflects heat back into the home and improves U-Factors.	0	0		0	0	0		0	0	0	Ö	D		0	0	0	
Low-E [®]	Outstanding overall performance for climates where both healing and cooling costs are a concern.	0	0		0	0	0	0	0	0	0		0	0	0	0	0	
Low-E with HeatLack Coating	Applied to the room-side surface, it reflects heat back into the home and improves U-Factors.		0		0		0	0	0	0	0	0	0		0	0	0	
Sun'	Outstanding thermal control in southern climates where less solar heat gain is desired	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	
PassiveSun [®]	ideal for northern, passive solar construction applications where solar heat gain is desired			(D)	0	0	0	0	0	0	0		0		0	0	0	
PassiveSun with HeatLack Coating	Applied to the room-side surface, it reflects heat back into the home and improves U-Factors.	0	0	0	0	0	0	0	0	0	0	()	0		0		0	
Clear Dual-Pane	High visibility with basic freemal performance.		0	0	0	0	0	0	0		0	0	0	0	0	0	0	

ADDITIONAL GLASS OPTIONS

Tempered safety glass, standard on patio doors. Obscure patterned glass to let in light while obscuring vision.

Blinds-Between-the-Glass are located between the panes of insulated glass, protected from dust and damag and never need cleaning. White blinds are available on select Perma-Shield® gliding patio doors.



WINDOW HARDWARE



CLASSIC SERIES STANDARD

Gliding

Verilock® security sensors and wireless open/closed sensors are available with select products. Visit andersenwindows.com/connect to learn more

10