VILLAGE OF DOBBS FERRY

SITE PLAN CHECK LIST

The items listed below should be reviewed by the applicant's design professional to aid in providing a complete submission.

<u>AG</u>	ENCY APPROVALS	<u>YES</u>	<u>NO</u>
Wes	stchester County Department of Health		
	tic and Water.		
-	York State Department Environmental	 	
	servation Stormwater SPDES.		
Nev	V York City Department Environmental	 	
Prot	ection Joint Septic.		
Nev	V York City Department of Environmental		
	ection SWPPP.		
<u>VIL</u>	LAGE PERMITS/APPROVALS		
Zon	ing Board of Appeals.		
Blas	sting and Explosives Permit.		
Fill	Permit.		
Fres	hwater Wetlands Permit.		
Site	Plan to comply with Subdivision		
Pla	t approval requirements		
Stormwater Pollution Prevention Plan (SWPPP)			
Arc	hitectural Review		
Buil	ding Permit		
Exc	avation/Grading Pernit		
Den	nolition Permit		
Elec	etrical Permit		
<u>SIT</u>	E PLAN INFORMATION		
1.	24" x 36" maximum drawing size.		
2.	Minimum scale: $(1" = 30')$.		
3.	Project Name.		
4.	Name and address of engineer and surveyor.		
5.	Name and address of owner of record and applicant.		
6.	Drawings signed and sealed by P.E. or R.A.		
7.	Original drawing date & revision dates.		
8	Tax man section and lot numbers.		

9.	Location plan with existing and adjacent zoning district. Scale, north arrow, date of survey, property acreage, drawings numbered (i.e., 1 of 3, 2 of 3, etc.) & identify adjoining property owners.	_	
11. 12.	Minimum yard setbacks. Provide bulk zoning table with all existing, proposed and required conditions.		
<u>AGI</u>	ENCY APPROVALS		
12.	Estimated quantity of cut or fill to be imported or removed from site or provide note stating that ANo material is to be imported or removed from this site.@		
13.	Topography at two feet maximum intervals.		
14.	Topography along streets adjacent to property.		
15.	Existing buildings, retaining walls, fences, rock outcrops, wooded areas, watercourses, water bodies, wetlands and wetland controlled areas, etc.		
16.	Total amount of site area disturbed		
<u>DRA</u>	INAGE To be provided at a later date.		
1.	Collect and convey driveway runoff. Mitigate increases in site runoff due to site development.		
2.	Roof drains to discharge to existing or proposed drainage system. Mitigate increases from roof runoff.		
3.	Surface inlets provided where low points cannot be graded to drain.		
4.	Swale provided between buildings and embankment which slopes toward building.		
5.	Culverts provided where roads or driveways cross watercourses.	,	
6.	Catch basin spacing adequate.		
7.	All rim and invert elevations provided.		
8.	Two feet minimum cover of storm drains in roads, driveways and parking areas. 18" minimum elsewhere.		
9.	Drywells provided with emergency overflow outlet pipes to grade. Multiple drywell systems should be connected by equalization pipes with rim and invert elevations posted.		
10	Minimum storm drain nine size 15" diameter		

11.	Headwalls or end sections provided at pipe inlets and outlets.			
12.	Rip-rap provided at headwalls and end sections.			
13.	Provide cross section for pond or detention facility.			
10.	Trovide cross section for point or determion facility.			
SITI	E INGRESS/EGRESS			
1.	Adequate sight distance at driveway intersection			
2	with road. —			
2.	Site accessible to fire trucks, emergency			
	vehicles, tractor trailers for fill deliveries,			
2	moving vans, oil trucks, etc.			
3.	Backup space for parking area.			
4.	Driveways intersecting existing road at 90E.			
SITE	E GRADING			
1.	All proposed grading on property for house, driveway			
	and septic. Show limit line of disturbance.			
2.	Driveway platform sloped at 4% maximum within			
	25 feet of centerline of street or within 35 feet from		N	/ Z
	the Right-of-Way, whichever is the greater distance.			
3.	Driveway slope 14% maximum.		N	
4.	Parking area 5% maximum.		N	
5.	Paved areas 1% minimum grade at curb line.		N	/ <i>P</i>
6.	Lawn area 2% minimum.			
7.	Top and bottom of retaining wall elevations provided.			
8.	Outside grade pitched away from residence.			
9.	Guide rail provided at steep drop offs.			
10.	Spot elevations at corners of residence and parking area			
	where necessary to ensure positive drainage.			
11.	Finished floor elevations provided including basement.			
12.	Plans and calculations for walls ≥ 4 feet Signed & Sealed by P.E., R.A.			
13.	Provide profiles of proposed roads with vertical			
14.	geometry. Provide horizontal geometry.			
. T.	i iovido nonzontai geometry.			
<u>GEN</u>	RAL			
1.	Show existing and proposed utilities(water, sewer,etc.)			
2.	Show snow piling areas.		N/ <i>P</i>	Ā

3.	Show refuse areas with enclosures.		
4.	Show zoning map with districts(school, fire, etc).		
5.	Show signage.		
6.	Show landscaping.		
7.	Provide sections and details of wall.		
8.	Provide phasing plan for areas over 5ac.		
9.	Provide lighting plan. To be provided at a later date.		
10.	Maintain low noise level at property line.		
11.	ADA compliance		
12.	-Village Construction Standard Compliance		
SITE	PLAN NOTES To be provided at a later date.		
1.	General construction notes.		
2.	Construction Sequence shown on plans.		
3.	The following notes shall be provided on the plans:		
	AShould rock blasting be required, a permit		
	application in accordance with Chapter 125 -		
	Blasting and Explosives of the Village of Dobbs		
	Ferry Code must be submitted to the Village by		
	the applicant for review/approval. This should		
	be noted on the plans as follows:		
	,		
	AThe Village Engineer may require additional		
	erosion control measures if deemed appropriate		
	to mitigate unforeseen siltation and erosion of		
	disturbed soils.@		
	· · · · · · · · · · · · · · · · · · ·		
	AAs-Built plans of the proposed driveway and		
	drainage improvements shall be submitted to		
	the Village Engineer for review prior to issuance		
	of Certificate of Occupancy.@		
	AFill material imported to the site shall be		
	certified in writing by a New York Licensed		
	Professional Engineer as clean, non-contaminated		
	fill suitable for the intended use.		
	and beamone for the internation approx		
	"Defere the site plan is signed by the Chairman of		
	"Before the site plan is signed by the Chairman of the Planning Board, the applicant shall be required		
	to post a performance bond or other type of		
	to post a performance bond of other type of		

		acceptable monetary guaranty which shall be in an amount determined by the Planning Board and the Village Engineer and in a form satisfactory to the Village Attorney".		
4. T	The follow	wing notes shall be provided on plans that involve SWPPP's	:	
	Villag	pplicant shall notify the Building Department ore's Consulting Engineer in writing at least 48 hours before the following so that any inspection may be performed.		
	1)	Start of construction		
	2)	Installation of sediment and erosion control measures.		
	3)	Completion of site clearing.		
	4)	Completion of rough grading.		
	5)	Installation of SMP's.		
	6)	Completion of final grading and stabilization of distured areas.		
	7)	Closure of construction.		
	8)	Completion of final landscaping; and		
	9)	Successful establishment of landscaping in public areas.		
	inspec sedim at leas	owner or operator shall have a qualified inspector t and document the effectiveness of all erosion and entation control practices and prepare inspection reports at once a month. These reports must be kept on site and ole for review".		
SITE	CONST	TRUCTION DETAILS To be provided at a later date.		
Drive	way Pro	file		

Driv	veway and shoulder section		
Roa	adway replacement		
Pav	rement section		
Side	ewalk Details		
Rip-	-rap slopes, embankments and aprons		
Pav	ed, rip-rapped, grass gutters		
	SDOT material item numbers		
Dete	ention basin		
Cato	ch basin		
Surf	face inlet —		
Drai	in manhole		
Hea	ndwall		
Curl	ъ		
	well		
-	derdrain		
	aining wall		
	fence		
	rbales		
	t protection		
	i-tracking strip		
	derail		
	rgy dissipater		
	iment traps or basins	-	
bcui	mient traps of vasins		
ERO	OSION CONTROL PLAN To be provided at a later	date.	
Eros	sion control measures implemented as per New	York	
Guio	delines for Urban Erosion and Sediment Control		
MIS	SCELLANEOUS ITEMS		
1.	Proposed easements		
	a) Temporary construction		
	b) Drainage		<u> </u>
	c) Sight		
	d) Slope		
	e) Driveway access		
	-,		
2.	Existing sanitary disposal system in the vicin	ity	
	of construction activity protected with tempo		
	fencing.	·	